


Specifications

Model Name	PNHS431	PNHS501	PNHS551
Installation	Landscape / Portrait / Face-up / Face-down / Tilt-forward / Tilt-backward		
LCD Panel	43" class (42 1/2" diagonal) TFT LCD	50" class (49 1/2" diagonal) TFT LCD	55" class (54 5/8" diagonal) TFT LCD
Backlight	LED, full array		
Max. Resolution	3,840 × 2,160 pixels		
Max. Display Colours (approx.)	1,070 million colours		
Pixel Pitch (H × V)	0.2451 × 0.2451 mm	0.2854 × 0.2854 mm	0.315 × 0.315 mm
Max Brightness* ¹	700 cd/m ²		
Contrast Ratio	1,200 : 1	4,000 : 1	5,000 : 1
Viewing Angle (H/V)	178°/178° (CR≥10)		
Active Screen Area (W × H)	37 1/16" × 20 13/16"	43 1/8" × 24 1/4"	47 5/8" × 26 13/16"
Response Time	8ms (grey to grey, avg.)		
Video	Analog RGB (0.7 Vp-p) [75Ω]		
Computer Input	Horizontal/vertical separation (TTL: positive/negative)		
Synchronization	VESA DDC2B		
Plug & Play			
Input Terminals* ²	Mini D-sub 15-pin × 1, HDMI × 3		
Audio	3.5mm mini stereo jack × 1		
Serial (RS-232C)	D-sub 9 pin × 1		
Output Terminals* ²	-		
Video	RCA pin (L/R) × 1		
Audio	D-sub 9 pin × 1		
Serial (RS-232C)	USB port (2.0 - compliant) × 1		
USB Port	10Base-T/100Base-TX		
LAN Terminal	10W + 10W		
Speakers Output	AC 100 - 240 V, 50/60 Hz		
Power Requirement	4 points, 400 × 400 mm pitch, M6 screw		
Mounting	4 points, 200 × 200 mm pitch, M6 screw		
Environmental Conditions	Operating Temperature* ³		
Operating Humidity	32°F to 104°F (0°C to 40°C)		
Power Consumption (Input signal waiting state/standby mode* ⁴)	20% to 80% (no condensation)		
Dimensions (approx.)	140 W (1W / 0.5W)	150 W (1W / 0.5W)	190 W (1W / 0.5W)
Weight (approx.)	38 5/16" × 2 1/2" × 22 1/8"	44 7/16" × 2 1/2" × 25 9/16"	48 7/8" × 2 1/2" × 28 1/16"
	25.4 lbs	33.1 lbs	39.7 lbs


*¹ Brightness depends on input mode and other picture settings. Brightness level will decrease over time. Due to the nature of the equipment, it is not possible to precisely maintain a constant level of brightness.
*² Use a commercially available connection cable for PC and other video connections. *³ When using the monitor lying flat on a surface (or when the monitor is tilted more than 20 degrees upward or downward from the perpendicular in relation to a level surface) the ambient temperature must be within the range of 0°C to 30°C. Temperature conditions may change when using the monitor together with optional equipment. In such cases, check the temperature conditions specified by the optional equipment. *⁴ No optional part is attached.

Dimensions


PNHS431



PNHS501




PNHS551




Input/Output Terminals

Bottom (when placed horizontally)



Left side* (when placed horizontally) *When viewed from the front



Units: inch (mm)

SHARP
Be Original.

SHARP ELECTRONICS OF CANADA LTD.
335 Britannia Road East,
Mississauga, Ontario L4Z 1W9
1-800-567-4277 • www.sharp.ca

Printed in Canada.
VSG-VS-PNHS-E-PDF-01/2022

© 2022 Sharp Electronics of Canada Ltd. All rights reserved.

Sharp is a registered trademark of Sharp Corporation and/or its affiliated companies. The terms HDMI, HDMI High-Definition Multimedia Interface and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. All other brand names and product names may be trademarks or registered trademarks of their respective owners. All screen images appearing in this brochure are simulated. Design and specifications are subject to change without prior notice.

HDMI
HIGH-DEFINITION MULTIMEDIA INTERFACE