

LED-FC015i-137

137" Indoor LED 1.58mm Full HD Bundle



Nothing less than magnificent

The Sharp FC Series provides stunning visuals in a durable package designed for high traffic environments. This 137" FHD kit is built with Sharp's 1.58mm LED-FC015i module designed for vibrant and colourful content visualization and is ideal for viewing from 3 ft. to 8 ft. away. The FC Series delivers unmatched brightness among fine-pitch DvLEDs. The added durability makes the FC series the ideal solution for retail, transportation, museums, public spaces and more. The FC Series is engineered with the latest flip chip COB technology that deliver immersive visuals in a durable package and have no external cables required for installation. The front serviceable design allows for easy access and quick maintenance when needed. Sharp offers full planning and design, installation and post installation maintenance support, ensuring you get a custom tailored solution allowing you to focus on what's most important – your business.

Benefits

Durable Construction - Ensures peace of mind operating in high-traffic environments.

16:9 Aspect Ratio – enabling standard Full HD content to be utilized, saving time and cost in content creation.

Quality Product – designed and tested in Germany, LED fine pitch product of the highest quality.

Ultimate Versatility – small 16:9 modules allowing excellent flexibility within the available space.


Excellent Homogeneity – uniform colour and brightness across the entire wall.

Outstanding Picture Quality – COB (Flip Chip) Multi-Colour LEDs provide unmatched contrast and brightness in a durable, reliable package.

| Direct View LED Module | | LED-FC015i-137 |
|--------------------------|--|---|
| Display | Panel Technology | Direct View LED |
| | Pixel Configuration | COB (Flip Chip) |
| | Panel Resolution | 1920 x 1080 |
| | Aspect Ratio | 16:9 |
| | Pixel Pitch | 1.58mm |
| | Brightness (typical) | 800 cd/m ² |
| | Contrast Ratio (typical) | 20000:1 |
| | Viewing Angle (typical) | 80/80 horizontal / 80/80 vertical |
| | Dimming Capability | 256 levels |
| | Colour Processing | Up to 16 bit |
| | Displayable Colours | 281 Trillion |
| | Refresh Rate | Up to 3840 Hz |
| | Lifetime | 100,000 Hours* |
| Connectivity | Input Terminals Digital | 1 x 3G SDI; 1 x DVI-D; 1 x HDMI |
| | External Control | 1 x GenLock; 1 x LAN |
| Power Consumption | On (typical) | 900 Watts |
| | Max | 1625 Watts |
| Physical Specifications | Dimensions (W x H x D) | 121.3 x 72.1 x 3.2in / 3080 x 1831.5 x 82mm |
| | Weight (Net) | 515.9lbs / 234.0kg |
| Environmental Conditions | Operating Temperature | -4° to 104°F / -20° to 40°C |
| | Operating Humidity | 10% to 80% |
| | Storage Temperature | -4° to 113°F / -20° to 45°C |
| | Storage Humidity | 10% to 85% |
| | IP Rating | IP40 |
| Ships With | 1x LED Controller, LED Modules (25 Cabinets, 200 Pixel Cards), Overframe Kit (5x5), Pixel Card Removal Tool, Power Bar; 7% Spare Parts Kit, Wall mount (5x5) | |
| Limited Warranty | 3 years | |

*Does not constitute a warranty beyond the three year limited warranty period.

Every bundle ships with



LED Modules



Power Bar




Overframe



Pixel Card Removal Tool



Spare Parts



Wallmount



LED Controller

SHARP
Be Original.

SHARP ELECTRONICS OF CANADA LTD.
335 Britannia Road East, Ste. 101
Mississauga, Ontario L4Z 1W9
1-800-567-4277 • www.sharp.ca

Printed in Canada.
VSG-VS-FC-E-PDF-08/2024

©2024 Sharp Electronics of Canada Ltd. All rights reserved. Prices, design, and specifications subject to change without notice. Sharp and related trademarks are trademarks or registered trademarks of Sharp Corporation. All other brand names and product names may be trademarks or registered trademarks of their respective owners. Screen images are simulated.