

LED-FE012i3-110

110" Indoor LED 1.26mm Full HD Bundle



Nothing less than magnificent

Sharp's fine pitch LED FE Series 3 bundles provide uncompromising LED imaging in a power-efficient, cost-effective package. With unmatched power efficiency among SMDs and improved contrast and colour gamut coverage, the FE Series 3 delivers content that gets noticed. Designed with high quality components and maintenance access from the front, the FE Series provides a display solution with longevity and good return on investment. The FE Series 3 bundles are the prime solution for boardrooms, auditoriums, retail, and airport signage. The FE Series 3 boasts a total installation depth of just 3.2 in., plus complete internal cabling, the FE Series presents a sleek profile for a bezel-free viewing experience. This Full HD bundle is designed for viewing from 3 ft. to an optimal 7 ft. and includes everything required to install an LED wall, including a power bar, framing, mounting and controller.

Benefits

Innovative 3 in 1 Flip Chip SMD Multi-Colour LEDs – provide improved performance with up to 60% less power consumption compared to traditional SMDs.

Quality product – designed and tested in Germany, LED fine pitch product of the highest quality.

Ultimate Versatility – small 16:9 modules allowing excellent flexibility within the available space.

Secure Investment – the intelligent cabinet design allows for upgrade to higher resolutions.


Excellent Homogeneity – uniform colour and brightness across the entire wall.

Outstanding Picture Quality – through the use of Multi-Colour LEDs.

Direct View LED Kit		LED-FE012i3-110
Display	Panel Technology	Direct View LED
	Pixel Configuration	3-1 SMD (Black)
	Panel Resolution	1920 x 1080
	Aspect Ratio	16:9
	Pixel Pitch	1.26mm
	Brightness (typical)	700 cd/m ²
	Contrast Ratio (typical)	8000:1
	Viewing Angle (typical)	85/85 horizontal / 80/80 vertical
	Dimming Capability	256 levels
	Colour Processing	Up to 16 bit
	Displayable Colours	281 Trillion
	Colour Gamut (cover ratio)	Adobe: 99.9 / DCI: 98.4
	Refresh Rate	Up to 3840 Hz
	Lifetime (typical)	100,000 Hours*
Connectivity	Input Terminals Digital	1 x 3G SDI; 1 x DVI-D; 1 x HDMI
	External Control	1 x GenLock; 1 x LAN
Power Consumption	On (typical)	352 Watts
	Max	608 Watts
Physical Specifications	Dimensions (W x H x D)	97.3 x 58.6 x 3.2 in / 2472 x 1488 x 81 mm
	Weight (Net)	419.1 lbs / 190.1 kg
Environmental Conditions	Operating Temperature	-4° to 104°F / -20° to 40°C
	Operating Humidity	10% to 80%
	Storage Temperature	-4° to 113°F / -20° to 45°C
	Storage Humidity	10% to 85%
	IP Rating	IP20
Ships With		1x LED Controller, LED Modules (16 Cabinets, 128 Pixel Cards), Overframe Kit (4x4), Pixel Card Removal Tool, Power Bar; 7% Spare Parts Kit, Wall Mount (4x4)
Limited Warranty		3 years

*Does not constitute a warranty beyond the three year limited warranty period.

Every bundle ships with



LED Modules



Power Bar




Overframe



Pixel Card Removal Tool



Spare Parts



Wallmount



LED Controller

SHARP
Be Original.

SHARP ELECTRONICS OF CANADA LTD.
335 Britannia Road East, Ste. 101
Mississauga, Ontario L4Z 1W9
1-800-567-4277 • www.sharp.ca

Printed in Canada.
VSG-VS-FE-E-PDF-07/2024

©2024 Sharp Electronics of Canada Ltd. All rights reserved. Prices, design, and specifications subject to change without notice. Sharp and related trademarks are trademarks or registered trademarks of Sharp Corporation. All other brand names and product names may be trademarks or registered trademarks of their respective owners. Screen images are simulated.