



# Say goodbye to dull, inconsistent displays

## Professionally Crafted for High-Impact Messaging

The Sharp MultiSync® PN-P Series is your trusted choice for bold, ultra-reliable digital signage—built to perform in environments with higher ambient lighting and extended runtime needs such as healthcare, command centres, finance, retail, and corporate settings. Featuring factory-calibrated colour precision, flexible performance options, and a tough all-metal chassis, these displays deliver stunning visuals and commercial-grade durability straight out of the box.

## Key Pain Points—Solved

**Tired of inconsistent colours across displays?** SpectraView™ Engine gives you pixel-perfect factory calibration and pro-level customization.

**Looking for more accurate colour reproduction?** These displays have wide colour gamut panels, allowing you access to a broader range compared to standard displays. This will give you more accurate colour reproduction for retail, corporate or education branding.

**Dealing with outdated or clunky setups?** Enjoy seamless modular upgrades with Intel® SDM and Raspberry Pi Compute Module 4 support.

**Struggling with overheating or display dimming?** Smart cooling tech keeps your visuals bright and your system protected.

**Need 24/7 uptime in tough environments?** Full metal build, active cooling, and secure LAN controls ensure long-term reliability.



## High-End UHD Visuals, All Day, Every Day

Get next-level clarity with native 3840 x 2160 resolution and anti-glare, high-haze glass across the entire PN-P Series lineup. Imagery and messaging can become more vivid and lifelike than ever before! Additionally, these models boast an impressive 700 cd/m<sup>2</sup> in brightness, ensuring that your message cuts through—even in high-ambient light spaces.




## Consistent Colour with SpectraView™ Engine

Pre-calibrated for luminance, white point, gamma, and uniformity, every PN-P display features SpectraView Engine Technology and is ready to go, right out of the box. Want deeper control? Through the SpectraView Engine, dial in white point with adjustments of 100k, select brightness based on luminance level, or even input your own CIE colour coordinates, giving users capabilities like never before. Bonus: backlight stabilization keeps your visuals looking fresh longer—no early fade-outs here. All of these features are specifically engineered to give you the best visual quality for an extended duration.



## Smarter Daisy Chaining & Multi-Display Sync

Connect up to 4 independent displays from one source thanks to DisplayPort 1.4 connectivity and HBR3 capabilities with Multi-Stream Transport (MST\*). MST capabilities can drive up to 4 independent displays from a single DisplayPort source by multiplexing several video streams into a single stream and sending it to the display that then acts as a branch device to demultiplex the signals into the original streams - ideal for menu boards, video walls, and synchronized signage. Additionally, the display can daisy chain the LAN connection, which allows for the pass-through of RS-232C, TCP/IP and IR communications. This gives the customer the ability to control full arrays of displays remotely or via the IR remote control, streamlining the ease of use for the customer.



\*MST capabilities depend on the video card driving the system.

## Power, Connect, Control—Simplified

Each PN-P product features an integrated USB hub, with a USB-C input that supports both DP-Alt mode and upstream data transfer. It includes two downstream USB ports (one USB-A and one USB-C) for connecting and managing peripherals. This built-in hub reduces the need for additional equipment, lowering overall setup costs. Additionally, the USB-C input provides 65W of Power Delivery, enabling devices like laptops to charge directly from the display—ideal for huddle spaces and presentation environments.




## Commercial Toughness You Can Trust

A full-metal chassis, carrying handles, and an active cooling system mean it's ready for harsh environments without compromising the sleek design. Integrated temperature sensors keep your brightness consistent without thermal dimming - your content stays front and centre, even in the harsher conditions found in commercial environments.



### Built for Flexibility


The MultiSync PN-P Series is modular by design, ready to integrate Intel® Smart Display Modules (SDM-L/SDM-S) and Raspberry Pi Compute Module 4 for embedded intelligence without external gear or messy cabling. Through clever mechanical and electrical design, the PN-P Series allows for sleek all-in-one intelligence and interoperability in a small form factor setting, giving you everything you need for digital signage applications while also offering the ability to enhance your screen through multiple integrated professional technologies - all while simplifying installations and allowing for clean and easy set-up.



### Smart Input Prioritization


Auto-switch between up to three prioritized inputs or power on with a live signal - no more blank screens or manual resets. If a primary source goes down, the display will automatically switch to whatever the customer has prioritized next. The first detect First Detect option also allows for the display to automatically switch to any source that plugs into it, allowing the display to wake on any synced signal.

#### Typical Display



### Built-in Security for IT Peace of Mind

With IEEE802.1x authentication via the LAN connection, SSL/TLS browser control, LAN and USB port disabling, and MAC/IP filtering, the MultiSync PN-P Series helps keep your network secure and locked down.



#### PN-P Series



### Total Control with NaViSet Administrator™

Remotely manage all your PN-P Series - and other Sharp or NEC displays - from a single, centralized dashboard using NaViSet Administrator 2™. Perfect for multi-display setups, this free tool lets you monitor status, automate tasks, generate reports, and make on-demand changes from anywhere. Want even more power? Upgrade to the Server Edition for enhanced features and full remote access across your ecosystem.



**NaViSet**  
Administrator 2



#### First Detect




### Bottom Line:

The Sharp MultiSync PN-P Series brings next-gen display power, all-day reliability, and built-in flexibility—wrapped in a clean, modern design that makes your content pop. Whether you're running a control room or creating an unforgettable retail experience, the PN-P Series is here to boost your signage game and keep it fresh 24/7.

## Specifications

Model		PN-P556	PN-P656
LCD Module	Panel Technology	IPS	
	Viewable Image Size	54.6"	64.5"
	Native Resolution	3840 x 2160	
	Brightness (Typical)	700 cd/m <sup>2</sup>	
	Contrast Ratio (Typical)	1200:1	
	Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10	
	Aspect Ratio	16:9	
	Colour Gamut	92% DCI	
	Displayable Colours	Over 1.07 Billion (10bit dithered)	
	Orientation	Landscape and Portrait (CCW Rotation)	
Panel Haze (%)		25	
Connectivity	Input Terminals	Digital	HDMI 2.0 x2, DP 1.4 x1, USB-C (Upstream with DP-Alt Mode and 65W Power Delivery)
		Analog	N/A
		Audio	N/A
		External Control	LAN (100Mbit), 3.5mm Mini Jack IR Remote, RS-232C
		Data	USB-C (Upstream with DP-Alt Mode and 65W Power Delivery), USB-A 2.0 (Service), USB-A (Downstream), USB-C (Downstream)
	Output Terminals	Digital	HDMI x1, DisplayPort x1 (Carries DP or DP-Alt signals via USB-C)
		Analog	N/A
		Audio	3.5mm Mini Jack
		External Control	LAN (100Mbit, carries RS-232C and IR)
		On (Typ/Max Brightness/All Max)	
Network Standby		0.5W	
Normal Standby		2W	
Current Rating		4.1A - 1.7A @ 100V - 240V	5.0A - 2.1A @ 100V - 240V
Speaker Rating		Optional through SP-RM3a	
Bezel Width (L/R,T/B)		11.0mm/11.0mm, 11.0mm/13.9mm	
Physical Specifications	Net Dimensions (Without stand; W x H x D)	48.7 x 27.9 x 2.3 in. 1235.6 x 709.3 x 59.5mm	57.3 x 32.8 x 2.3 in. 1454.5 x 832.4 x 59.5mm
	Net Weight	20.5kg/45.2lbs.	26.0kg/57.3lbs
	VESA Hole Configuration	4 x M6 (300 x 300)	4 x M6 (400 x 400)
	Ambient Light Sensor		Integrated
Sensors	Human Sensor		Optional through PN-KTRC3
	Temperature Sensor		Integrated and programmable; linked to cooling fans
	NFC Sensor		N/A
	Operating Temperature		0°C to 40°C
Environmental Conditions	Operating Humidity		20-80%
	Operating Altitude		3000m (9843ft)
	Limited Warranty		5 years Advanced Replacement
Additional Features		AMX Support, CEC Support through HDMI, Crestron Connected V2 Support with XiO Cloud, IEEE802.1x Wired Network Authentication, SSH, NaViSet Secure, Signed FW upon Install, Admin Login, IP Address Filtering, MAC Address Filtering, SNMP V1 /2/3, USB/LAN Lockout Capability, PD Comms Tool Support, NEC Firmware Update Tool, Display Browser Control, Display Wall Calibrator Compatible, HDR Support (PQ, HLG, HDR10), Key Guide, NaViSet Administrator 2 Compatible, OSD Rotation for Portrait Orientation, SDM Compatible, USB Power Delivery via USB-C (65W), Raspberry Pi Compute Module Compatible, Real-Time Clock, Local Dimming, Multi Picture Mode, SpectraView Engine Technology, Quick Start, Internet Time Server, Auto ID/IP Settings, Energy Star 8.0	
Ships With		3m AC Power Cord, 2.0m HDMI Cable, IR Remote Control, Batteries, AAA Batteries, Screw (M4 x10 with washer), Clamp, Optional Cover (SDM/CMIF)	
Optional Speakers		SP-RM3a	
Optional Stand		ST-65M / PN-ST55L	
Other Accessories		All SDM Option Cards, Raspberry Pi Compute Module 4 with optional NEC Interface Board, Human Sensor (PN-KTRC3)	



### Tabletop Stand

ST-65M / PN-ST55L (PN-P556/PN-P656)



### Wall Mount

WMK-3298T



Bottom Panel



### Input Panels

1. USB-A (Service)
2. Audio Mini Jack Out
3. LAN1 (Control In)
4. LAN2 (Control Out)
5. IR Remote IN
6. HDMI IN2
7. HDMI Out
8. HDMI IN1 (ARC)
9. DisplayPort In
10. DisplayPort Out
11. USB-C1 (Upstream, DP-Alt Mode, 65W PD)
12. USB-A (2.0/3.2 Gen1, Downstream)
13. USB-C2 (2.0/3.2 Gen1, Downstream)
14. RS-232C In

Side Panel



Visit [www.sharp.ca](http://www.sharp.ca) for details.



# SHARP

SHARP ELECTRONICS OF CANADA LTD.  
5995 Avebury Road, Suite 900  
Mississauga, Ontario L5R 3P9  
1-800-567-4277 • [www.sharp.ca](http://www.sharp.ca)

Printed in Canada.  
VSG-VS-PNP-B-E-PDF-10/2025

The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License. Sharp, MultiSync, NaViSet and TileMatrix and all related trademarks are trademarks or registered trademarks of Sharp Corporation and/or its affiliated companies. The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. Crestron, the Crestron logo, Crestron Connected, and XiO Cloud are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. All other brand names and product names may be trademarks or registered trademarks of their respective owners. Design and specifications are subject to change without prior notice. Screen images are simulated.